



Product datasheet

Dock light
Type: PV 10

Contact:

Ronnenberger Straße 20
D-30989 Gehrdenphone +49 (0) 5108 879 270
fax +49 (0) 5108 879 2710info@promstahl.de
www.promstahl.de

General information

In general, the danger of accidents during loading and unloading is very high due to bad lighting of the docking area.

The PV 10 dock light is new in the PROMStahl product range. This LED spotlight is highly energy efficient compared to a standard light bulb. The LED lamp consumes up to 90% less energy to produce the same lighting results. LED lamps provide 100 % luminance immediately after switching them on. This characteristic is very important for docking stations. The spotlight is fixed to the bracing arms by means of a rotating bracket so that it is movable in all directions. The bracing arms and the spotlight are coated in yellow colour. The colour yellow has a strong signalling effect and attracts attention. This makes sure that the dock light is clearly perceptible at any time.

Technical characteristics

- LED-light: 24 V / 30 W
- Luminous flux: 4200 Lumen +/- 10%
- Color temperature: 4000 K
- Protection class: IP 65
- Operating voltage: 230 V AC
- Cable length: 1,5 m + 0,5 m
- incl. connector plug CEE 7/7
- weight 5,8 kg
- incl. two-part articulated bracket, length approx. 1m
- Lifetime: > 50000 hours



The housing is flexible and can hence be moved in all directions; it is fixed by means of adjustable screws.



The front cover consists of stainless steel and therefore is corrosion-resistant; moreover, it has a high impact resistance.



The housing is made of die-cast aluminium and is optimized such that the heat is efficiently dissipated away from the source so that maximum heat removal can be reached.